



EVPN to the host

Host multitenancy

Atilla de Groot

Atilla de Groot | Sr. Systems Engineer, HCIE #3494 | Cumulus Networks

Agenda



EVPN to the Host

- Multi tenancy use cases
- Deployment issues
- Host integration with EVPN
- Caveats and future work


Multi tenancy use cases

Virtualization environments



VM environments

- MLAG to hypervisors
- Vxlan between hosts
- Double overlay
- Dedicated network nodes




Multi tenancy use cases

VM deployment issues



Architecture issues

- MLAG to hypervisors
- Vxlan between hosts
- Double overlay
- Dedicated network nodes
- Orchestration problems






Multi tenancy use cases

Container environments

Container environments

- BGP to hosts
- Host route advertisement
- Docker management
- Container overlay




Multi tenancy use cases

Container deployment issues



Architecture issues

- Host networking
- Multi-tenancy
- IP prefix overlap
- ACL management




Host integration with EVPN

Open standards



EVPN on hosts

- Vlan aware bridge
- VRF in Linux kernel
- VxLAN
- Free Range Routing with EVPN
- Ifupdown2
- Iproute2



```
cumulus@server01:~$ uname -a
Linux server01 4.17.0-041700-generic #201806041953 SMP Mon
Jun 4 19:55:25 UTC 2018 x86_64 x86_64 x86_64 GNU/Linux
```

```
cumulus@server01:~$ vrf list
```

VRF	Table

mgmt	1001
tenant3	1002
tenant2	1003
tenant1	1004



Host integration with EVPN

Host connectivity

Host connectivity

- Routing to hosts
- BGP unnumbered
- RFC5549
- Loopback advertisement
- EVPN address family

```
auto eth1  
iface eth1
```

```
auto eth2  
iface eth2
```

```
interface eth1  
  ipv6 nd ra-interval 10  
  no ipv6 nd suppress-ra  
interface eth2  
  ipv6 nd ra-interval 10  
  no ipv6 nd suppress-ra
```

```
router bgp 65501  
  bgp router-id 10.250.250.1  
  bgp bestpath as-path multipath-relax  
  neighbor FABRIC peer-group  
  neighbor FABRIC remote-as external  
  neighbor FABRIC timers 1 3  
  neighbor eth1 interface peer-group FABRIC  
  neighbor eth2 interface peer-group FABRIC  
!  
  address-family ipv4 unicast  
    redistribute connected route-map loopbacks  
    exit-address-family  
!  
  address-family l2vpn evpn  
    neighbor FABRIC activate  
    advertise-all-vni  
    advertise ipv4 unicast  
    advertise ipv6 unicast  
    exit-address-family  
!  
  route-map loopbacks permit 10  
    match interface lo
```


Host integration with EVPN

L2 tenancy



L2 tenancy

- Vlan-aware bridge
- ARP / ND suppression
- L2VNIs
- EVPN Type-2




Host integration with EVPN

Distributed routing



Distributed routing

- Gateway location
- SVIs on host
- Anycast gateway
- Local host routing




Host integration with EVPN

L3 tenancy



L3 tenancy

- VRFs on host
- Prefix advertisement
- L3VNIs
- EVPN Type-5




Host integration with EVPN

Container integration



Container integration

- Container IP redistribution
- Host route advertisement
- Prefix overlap
- No ACLs for tenant segregation




Host integration with EVPN

Bare metal integration



Bare metal integration

- Integration with RFC standard
- L2 stretching
- L3 tenancy
- Distributed routing





Future work

Proof of technology

Proof of technology

- Commercial support
- Software / tools availability
 - Linux kernel
 - FRR
- Demo

```
cumulus@server01:~$ uname -a
Linux server01 4.17.0-041700-generic
#201806041953 SMP Mon Jun 4 19:55:25 UTC
2018 x86_64 x86_64 x86_64 GNU/Linux
```

```
cumulus@server01:~$ bridge vlan
port vlan ids
bridge 1 PVID Egress Untagged
1010
1011
1012
1013
1014
```

VRF	Table
mgmt	1001
tenant3	1002
tenant2	1003
tenant1	1004

```
cumulus@server01:~$ sudo vtysh -c "show bgp evpn vni"
      VNI      Type RD          Import RT          Export RT          Tenant VRF
* 101010    L2  10.250.250.1:5    65501:101010    65501:101010    tenant1
* 101012    L2  10.250.250.1:3    65501:101012    65501:101012    tenant2
* 101014    L2  10.250.250.1:7    65501:101014    65501:101014    tenant3
* 404001    L3  172.30.11.1:8     65501:404001    65501:404001    tenant1
* 404002    L3  172.30.13.1:9     65501:404002    65501:404002    tenant2
* 404003    L3  172.30.15.1:10    65501:404003    65501:404003    tenant3
```



Future work

Orchestration & Caveats

Orchestration

- Openstack neutron
- Kubernetes / Swarm
- Host / Network management

Head-end replication

- BUM anycast
- Merchant silicon limitations
- Multicast replication
- PIM-SM



Future work

Route leaking & Micro segmentation

Route-leaking

- Inter tenant traffic
- Service tenant
- FRR implementation

Micro segmentation

- Host traffic filtering
- Filtering with BPF
- Flowspec for ACL distribution




EVPN to host demo





Questions ?





Thank you!

Visit us at cumulusnetworks.com or follow us [@cumulusnetworks](https://twitter.com/cumulusnetworks)

© 2018 Cumulus Networks. Cumulus Networks, the Cumulus Networks Logo, and Cumulus Linux are trademarks or registered trademarks of Cumulus Networks, Inc. or its affiliates in the U.S. and other countries. Other names may be trademarks of their respective owners. The registered trademark Linux® is used pursuant to a sublicense from LMI, the exclusive licensee of Linus Torvalds, owner of the mark on a world-wide basis.