

# ARISTA


DENOG 14

## 400G-ZR(+) Real World Examples


Florian Hibler <[florian@arista.com](mailto:florian@arista.com)>  
Manager, Systems Engineering

# Optics Overview

# Optics & Cables: Broad Portfolio from 1G to 400G



# Optics & Cables: Broad Portfolio from 1G to 400G



# 400G ZR Metro

# 400G-ZR Transceiver Specifications

Channel Range (Tunable)	191.375 to 196.100 THz
Channel Grid	100GHz & 75GHz
Optical Connector Type	Duplex LC
Tx output power	> -10 dBm*
Min Tx OSNR	45 dB
Rx input power	-16 dBm to 0 dBm
Min Rx OSNR	> 26 dB
Pre-FEC BER threshold	1.0E-02
Forward Error Correction (FEC)	C-FEC
Max amplified reach **	120km
Max span loss **	25 dB
Min span loss	2 dB
Max chromatic dispersion	2400 ps/nm
Power consumption	16 W Typ, 20 W max
Max case temperature	75C

Frequency and Grid Spacing

Low Launch Power Amplification needed

Critical value to ensure error free signal


Critical value to ensure link stability

# Typical Fiber Specifications

## Single-mode fibre, E9/125/250, OS2 / G.652.D

### low attenuation

in accordance with ITU-T G.652.D, IEC 60793-2-50 Type B1.3, equates to EN 50173:2011 OS2



1 Core  
2 Cladding  
3 Coating

### OPTICAL PROPERTIES

#### Transmission characteristics



Wavelength	[nm]	1310	1383	1550	1625
Maximum attenuation (cabled)	[dB/km]	0.34	0.34*	0.21	0.23
*post hydrogen aging performance					
Maximum Chromatic Dispersion	[ps/(nm x km)]	3,5		18	23
Zero Dispersion Wavelength $\lambda_0$	[nm]	$1304 \leq \lambda_0 \leq 1324$			
Maximim Zero Dispersion Slope $S_0$	[ps/(nm <sup>2</sup> x km)]	0.092			
Mode-Filed Diameter	[ $\mu$ m]	9.2 +/- 0.4		10.4 +/- 0.5	
Maximum Cable Cut-off Wavelength $\lambda_{CC}$	[nm]	1260			
<b>Polarisation Mode Dispersion</b>					
PMD Link Design Value	[ps/√km]	$\leq 0.04$			
Max. individual fibre PMD	[ps/√km]	$\leq 0.1$			
Max. individual cable PMD	[ps/√km]	$\leq 0.2$			
Refractive Index		1.4676		1.4682	

<0.25 dB/km required for ideal range

Typical value is around 17 ps/nm



# Optical Networking 101: Chromatic Dispersion

- Chromatic Dispersion is the phenomenon in which the phase velocity of a wave depends on its frequency
  - Different wavelength will travel at different speeds and hence broaden the overall signal




# Optical Networking 101: OSNR

- Optical signal-to-noise ratio (OSNR) is used to quantify the degree of optical noise interference on optical signals
  - Direct relationship between OSNR and bit error rate (BER)



$$\text{BER} = \frac{\text{no. of incorrect received bits}}{\text{no. of transmitted bits}}$$


# 400G-ZR / Point-to-Point for Metro Connections



# 400G-ZR / Configuration

```
SiteA# show interface status | grep ZR
Et34/1      connected  routed  full  400G  400GBASE-ZR
Et35/1      connected  trunk   full  400G  400GBASE-ZR
Et36/1      errdisabled 1       full  400G  AMP-ZR
```

```
interface Ethernet34/1
  description To_SiteB
  no switchport
  ip address 10.1.34.1/24
  transceiver frequency 193100.000
  transceiver transmitter signal-power -10.00
!
interface Ethernet35/1
  description To_SiteB
  switchport mode trunk
  transceiver frequency 193300.000
  transceiver transmitter signal-power -10.00
```



Data Center Interconnect using 400G-ZR optical modules and the OSFP-LS

**400G-ZR optics are tunable (coherent)  
You define the frequency per optic**

# 400G-ZR / 80 km / Transceiver

```
SiteB# sh int et 34/1 transceiver dom
Ch: Channel, N/A: not applicable, TX: transmit, RX: receive
mA: milliamperes, dBm: decibels (milliwatts), C: Celsius, V: Volts
Port 34
Last update: 0:00:05 ago
```

	Value
Case temperature	58.00 C
Voltage	3.30 V
TX power	-9.94 dBm
RX total power	-1.75 dBm
RX channel power	-8.90 dBm
Pre-FEC BER	4.28e-03
Post-FEC errored frames ratio	0.00e+00
Chromatic dispersion (short link)	-1384.00 ps/nm
Differential group delay	4.00 ps
SOPMD	43.00 ps^2
Polarization dependent loss	0.70 dB
Received OSNR estimate	26.70 dB
Received ESNR estimate	15.80 dB
Carrier frequency offset	112.00 MHz
SOP rate of change	0.00 krad/s
Laser temperature	49.21 C
Laser frequency	193100.00 GHz

Post-FEC errored frames ratio is very important

Same calculation as for the previous link

$1384/17=81.41$  km

Configured laser frequency


# 400G-ZR / 80 km / Line System DOM

SiteB# show line system port 36 dom thresholds

	Value	High Alarm Threshold	High Warn Threshold	Low Warn Threshold	Low Alarm Threshold	Unit	Indicator
Temperature	37.59	70.00	65.00	0.00	-5.00	C	
Voltage	3.28	3.47	3.37	3.23	3.14	V	
<b>Booster</b>							
Optical TX power (line)	9.46	16.99	16.53	-0.00	-6.03	dBm	
Optical RX power (local)	-16.50	-7.20	-8.23	-20.97	-23.98	dBm	
<b>Pre-amp</b>							
Optical TX power (local)	8.56	16.99	16.53	-0.00	-6.03	dBm	
Optical RX power (line)	-18.93	14.80	13.80	-19.21	-21.94	dBm	

SiteC# show line system port 36 dom thresholds

	Value	High Alarm Threshold	High Warn Threshold	Low Warn Threshold	Low Alarm Threshold	Unit	Indicator
Temperature	34.00	70.00	65.00	0.00	-5.00	C	
Voltage	3.31	3.47	3.37	3.23	3.14	V	
<b>Booster</b>							
Optical TX power (line)	9.10	16.99	16.53	-0.00	-6.03	dBm	
Optical RX power (local)	-16.99	-7.20	-8.23	-20.97	-23.98	dBm	
<b>Pre-amp</b>							
Optical TX power (local)	7.29	16.99	16.53	-0.00	-6.03	dBm	
Optical RX power (line)	-20.47	14.80	13.80	-19.21	-21.94	dBm	<b>WARN</b>



High attenuation on fiber in one direction



# 400G-ZR / FEC

- dB Loss Margin
  - C-FEC: 25 dB -> 100 km at 0.25 dB/km
  - O-FEC: 30 dB -> 120 km at 0.25 dB/km
  
- TX/RX dB loss of our 80 km fiber is 29.93 dB
  - 29.93 dB / 81.41 km -> **0.37 dB/km loss**

```
SiteB# show interfaces ethernet 34/1 error-correction
Interface          Configured          Available          Operational
-----          -
Ethernet34/1      Default            C-FEC, O-FEC      O-FEC
```

# Summary - 400G-ZR

## 400G-ZR


- 400G-ZR is a point-to-point <120km ONLY solution
  - No ROADMs or in-line amps
- Pre-amplification/booster available in Transceiver Form Factor
  - Extremely simple & cost effective, but cannot mix with other line systems
- 400G-ZR can work with external line systems, but customer needs to test & validate 3rd party line systems with their optical vendors

# 400G ZR+

## Longhaul / Global

# OpenZR+ MSA

- Open Industry standard for Long-haul Connections
- Key benefits of the 400G OpenZR+ MSA specification relative to 400-ZR are
  - 4x100GE multiplexing mode
  - Long-haul performance modes
  - Extended reach for dark fiber application



	400ZR	OpenROADM	OpenZR+
Target Application	Edge DCI	Carrier Metro/LH	Regional DCI
Client Traffic	400GbE only	100-400GbE & OTN	100-400GbE Multirate
Reach	<120km	>120km*	>120km*
Form Factor	QSFP-DD/OSFP	CFP2 or other	QSFP-DD/OSFP
SD-FEC	CFEC	oFEC	oFEC
Max Pwr Consumption	15W	Not Defined	20W*
Standards	OIF	OpenROADM	Leverages other standards work

# OpenZR+ Application Modes

- ZR+ transceiver supports multiple ‘application modes’ based upon the CMIS specification. Those INCLUDE 400ZR modes!

CMIS Application Code	Host format	Electrical interface	Payload	FEC	Modulation	Operating reach	MSA format
1	400GBASE-R	1x 400GAUI-8 (8x 50G)	400G	CFEC	DP-16QAM	80km	OIF 400ZR app code 0x01
2	400GBASE-R	1x 400GAUI-8 (8x 50G)	400G	CFEC	DP-16QAM	25km	OIF 400ZR app code 0x02
3	4 × 100GBASE-R	4x 100GAUI-2 (2x 50G)	400G	CFEC	DP-16QAM	80km	OIF 400ZR extension
4	400GBASE-R	1x 400GAUI-8 (8x 50G)	400G	oFEC	DP-16QAM	120km	OpenZR+ MSA (small PMD)
5	400GBASE-R	1x 400GAUI-8 (8x 50G)	400G	oFEC	DP-16QAM	450km	OpenZR+ MSA
6	4 × 100GBASE-R	4x 100GAUI-2 (2x 50G)	400G	oFEC	DP-16QAM	450km	OpenZR+ MSA
7	3 × 100GBASE-R	3x 100GAUI-2 (2x 50G)	300G	oFEC	DP-8QAM	600km	OpenZR+ MSA
8	400GBASE-R	1x 400GAUI-8 (8x 50G)	400G	oFEC	DP-16QAM	450km	OpenZR+ MSA
9	4 × 100GBASE-R	4x 100GAUI-2 (2x 50G)	400G	oFEC	DP-16QAM	450km	OpenZR+ MSA
10	3 × 100GBASE-R	3x 100GAUI-2 (2x 50G)	300G	oFEC	DP-8QAM	600km	OpenZR+ MSA
11	2x 100GBASE-R	2x 100GAUI-2 (2x 50G)	200G	oFEC	DP-QPSK	1000km	OpenZR+ MSA
12	2x 100GBASE-R	2 x CAUI4 (4x 25G) w/o FEC	200G	oFEC	DP-QPSK	1000km	OpenZR+ MSA
13	1x 100GBASE-R	1x 100GAUI-2 (2x 50G)	100G	oFEC	DP-QPSK	2000km	OpenZR+ MSA
14	1x 100GBASE-R	1 x CAUI4 (4x 25G) w/o FEC	100G	oFEC	DP-QPSK	2000km	OpenZR+ MSA

400G-ZR modes

OpenZR+ modes

# OpenZR+ Link Characteristics

- Each application mode depends on certain link characteristics.

Appl mode	Line rate	Host format	Tx Power <sup>1)</sup>	Rx sens @ high OSNR	Rx @ OSNR	Rx OSNR @0.5dB penalty	Rx OSNR @1dB penalty	CDC range
4	400G	1x 400GAUI-8	-10dBm to -6dBm	-20dBm	23.9dB@-12dBm	24.2dB@-14dBm	24.7dB@-16dBm	13 000ps/nm
5	400G	1x 400GAUI-8	-13dBm to -9dBm	-21dBm	23.4dB@-12dBm	23.9dB@-14dBm	24.4dB@-16dBm	13 000ps/nm
6	400G	4x 100GAUI-2	-13dBm to -9dBm	-21dBm	23.4dB@-12dBm	23.9dB@-14dBm	24.4dB@-16dBm	13 000ps/nm
7	300G	3x 100GAUI-2	-12dBm to -8dBm	-22dBm	20.3dB@-15dBm	20.8dB@-17dBm	21.3dB@-19dBm	26 000ps/nm
8	400G	1x 400GAUI-8	-13dBm to -9dBm	-21dBm	23.1dB@-12dBm	23.6dB@-14dBm	24.1dB@-16dBm	13 000ps/nm
9	400G	4x 100GAUI-2	-13dBm to -9dBm	-21dBm	23.1dB@-12dBm	23.6dB@-14dBm	24.1dB@-16dBm	13 000ps/nm
10	300G	3x 100GAUI-2	-12dBm to -8dBm	-23dBm	19.5dB@-15dBm	20.0dB@-17dBm	20.5dB@-19dBm	26 000ps/nm
11	200G	2x 100GAUI-2	-10.5dBm to -6.5dBm	-29dBm	15dB@-18dBm	15.5dB@-20dBm	16dB@-22dBm	50 000ps/nm
12	200G	2x CAUI4 w/o FEC	-10.5dBm to -6.5dBm	-29dBm	15dB@-18dBm	15.5dB@-20dBm	16dB@-22dBm	50 000ps/nm
13	100G	1x 100GAUI-2	-6dBm to -2dBm	-32dBm	11.8dB@-20dBm	12.3dB@-23dBm	12.8dB@-25dBm	50 000ps/nm
14	100G	1x CAUI4 w/o FEC	-6dBm to -2dBm	-32dBm	11.8dB@-20dBm	12.3dB@-23dBm	12.8dB@-25dBm	80 000ps/nm

1) The module transmit power can be provisioned up to the maximum available TX power. If the TX power is not provisioned by the host, the module TX power will default to the maximum available power, which can be any power level in the specified 4dB range.

# OpenZR+ Reach


- Reach is achieved by reducing line side speed and modulation
  - The values below are specified by OpenZR+, but might vary between transceiver vendors
- Type of amplification is crucial for 400G and 300G modes

OpenZR+ modes	EDFA-only (km)	EDFA and Raman amplifier (km)
400ZR+ (ZR400-OFEC-16QAM)	480	1040
300ZR+ (ZR300-OFEC-8QAM)	1600	2320
200ZR+ (ZR200-OFEC-QPSK)	2880	2880
100ZR+ (ZR100-OFEC-QPSK)	5840	5840

**Remember** - the line side mode has impact on how the service is presented to the switch (*CMIS application modes*)

# 400G-ZR+ / Point-to-Point for Longhaul Connections


- Brownfield deployment
  - Existing Nokia WDM
  - Pre-Amp(!) required
  - Arista 7280CR3-32D4
- ZR+ optics
  - SmartOptics ZR+ QSFP-DD (OEM from Acacia)
- 2 different links from the same switch
  - 40 km on red link
  - 750 km on green link



# 400G-ZR+ / 40 km / Interface configuration

```
SiteA# sh run int et 35/1
interface Ethernet35/1
  no switchport
  ip address 10.0.0.2/24
  transceiver power ignore
  transceiver application override 5
  transceiver frequency 193400.000
  transceiver transmitter signal-power -10.00
```

```
SiteA# sh int et 35/1 transceiver hardware
Name: Et35/1
Media type: 400GBASE-ZR
Maximum module power (W): 23.75 (Power limit check disabled)
Maximum slot power (W): 20.0
Configured frequency (GHz): 193400.0
Computed wavelength (nm): 1550.12
Operational frequency (GHz): 193,400.0
Operational wavelength (nm): 1550.12
Configured TX power (dBm): -10.0
Operational TX power (dBm): -10.0
```



Appl mode	Line rate	Host format	Tx Power <sup>1)</sup>	Rx sens @ high OSNR	Rx @ OSNR	Rx OSNR @0.5dB penalty	Rx OSNR @1dB penalty	CDC range
4	400G	1x 400GAUI-8	-10dBm to -6dBm	-20dBm	23.9dB@-12dBm	24.2dB@-14dBm	24.7dB@-16dBm	13 000ps/nm
5	400G	1x 400GAUI-8	-13dBm to -9dBm	-21dBm	23.4dB@-12dBm	23.9dB@-14dBm	24.4dB@-16dBm	13 000ps/nm
6	400G	4x 100GAUI-2	-13dBm to -9dBm	-21dBm	23.4dB@-12dBm	23.9dB@-14dBm	24.4dB@-16dBm	13 000ps/nm
7	300G	3x 100GAUI-2	-12dBm to -8dBm	-22dBm	20.3dB@-15dBm	20.8dB@-17dBm	21.3dB@-19dBm	26 000ps/nm
8	400G	1x 400GAUI-8	-13dBm to -9dBm	-21dBm	23.1dB@-12dBm	23.6dB@-14dBm	24.1dB@-16dBm	13 000ps/nm
9	400G	4x 100GAUI-2	-13dBm to -9dBm	-21dBm	23.1dB@-12dBm	23.6dB@-14dBm	24.1dB@-16dBm	13 000ps/nm
10	300G	3x 100GAUI-2	-12dBm to -8dBm	-23dBm	19.5dB@-15dBm	20.0dB@-17dBm	20.5dB@-19dBm	26 000ps/nm

# 400G-ZR+ / 40 km / Link status

```
SiteA# sh int et 35/1 transceiver dom
```

	Value
<b>Case temperature</b>	<b>54.00 C</b>
Voltage	3.19 V
TX power	-10.65 dBm
RX total power	-11.84 dBm
<b>RX channel power</b>	<b>-11.27 dBm</b>
Pre-FEC BER	2.12e-03
<b>Post-FEC errored frames ratio</b>	<b>0.00e+00</b>
<b>Chromatic dispersion (short link)</b>	<b>624.00 ps/nm</b>
Chromatic dispersion (long link)	620.00 ps/nm
Differential group delay	1.00 ps
SOPMD	32.00 ps^2
Polarization dependent loss	0.90 dB
<b>Received OSNR estimate</b>	<b>27.90 dB</b>
Received ESNR estimate	16.80 dB
Carrier frequency offset	-8.00 MHz
SOP rate of change	0.00 krad/s
Laser temperature	50.85 C
<b>Laser frequency</b>	<b>193400.00 GHz</b>

```
SiteA# sh transceiver status interface et 35/1 | grep Oper
Operational speed           400Gbps
```

```
SiteA# sh int et 35/1 phy detail
Ethernet35/1
```

	Current State
<b>Interface state</b>	<b>up</b>
Transceiver	400GBASE-ZR
<b>PHY state</b>	<b>linkUp</b>
<b>Oper speed</b>	<b>400Gbps</b>
<b>Lane count</b>	<b>8</b>
PCS RX link status	up
PCS RX fault	ok
PCS TX fault	ok
PCS BER	0
<b>Forward Error Correction</b>	<b>Reed-Solomon</b>
Reed-Solomon codeword size	544
PMA/PMD RX link status	up
PMA/PMD lane RX link status	
Lane 0	up
Lane 1	up
Lane 2	up
Lane 3	up
Lane 4	up
Lane 5	up
Lane 6	up
Lane 7	up

# 400G-ZR+ / 750 km / Interface configuration

```
SiteC#sh run section 36/  
interface Ethernet36/1  
  speed 100g-2  
  no switchport  
  transceiver power ignore  
  transceiver application override 7 lanes start 1  
  transceiver application override 7 lanes start 3  
  transceiver application override 7 lanes start 5  
  transceiver frequency 192275.000  
  transceiver transmitter signal-power -10.00  
interface Ethernet36/3  
  speed 100g-2  
  no switchport  
interface Ethernet36/5  
  speed 100g-2  
  no switchport  
interface Ethernet36/7  
  speed 100g-2  
  no switchport
```

```
SiteC#sh interfaces et36/1 transceiver hardware  
Name: Et36/1  
Media type: 400GBASE-ZR  
Maximum module power (W): 23.75 (Power limit check disabled)  
Maximum slot power (W): 20.0  
Configured frequency (GHz): 192275.0  
Computed wavelength (nm): 1559.19  
Operational frequency (GHz): 192,275.0  
Operational wavelength (nm): 1559.19  
Configured TX power (dBm): -10.0  
Operational TX power (dBm): -10.0
```

Appl mode	Line rate	Host format
4	400G	1x 400GAUI-8
5	400G	1x 400GAUI-8
6	400G	4x 100GAUI-2
7	300G	3x 100GAUI-2
8	400G	1x 400GAUI-8
9	400G	4x 100GAUI-2
10	300G	3x 100GAUI-2

# 400G-ZR+ / 750 km / Link status

```
SiteA# sh int et 36/1 transceiver dom
```

```

Value
-----
Case temperature          50.00 C
Voltage                   3.19 V
TX power                  -10.22 dBm
RX total power            -7.80 dBm
RX channel power          -11.43 dBm
Pre-FEC BER               5.73e-03
Post-FEC errored frames ratio 0.00e+00
Chromatic dispersion (short link) 12674.00 ps/nm
Chromatic dispersion (long link) 12660.00 ps/nm
Differential group delay  1.00 ps
SOPMD                     51.00 ps^2
Polarization dependent loss 1.20 dB
Received OSNR estimate     21.50 dB
Received ESNR estimate     12.40 dB
Carrier frequency offset   131.00 MHz
SOP rate of change         0.00 krad/s
Laser temperature          49.68 C
Laser frequency            193000.00 GHz

```

```
SiteA# sh transceiver status | i 36/
```

```

Et36/1    connected    routed    full    100G    400GBASE-ZR
Et36/3    connected    routed    full    100G    400GBASE-ZR
Et36/5    connected    routed    full    100G    400GBASE-ZR
Et36/7    notconnect    routed    full    100G    400GBASE-ZR

```

Appl mode	Line rate	Host format
4	400G	1x 400GAUI-8
5	400G	1x 400GAUI-8
6	400G	4x 100GAUI-2
7	300G	3x 100GAUI-2
8	400G	1x 400GAUI-8
9	400G	4x 100GAUI-2
10	300G	3x 100GAUI-2


Appl mode	Line rate	Host format	Tx Power 1)	Rx sens @ high OSNR	Rx @ OSNR	Rx OSNR @0.5dB penalty	Rx OSNR @1dB penalty	CDC range
7	300G	3x 100GAUI-2	-12dBm to -8dBm	-22dBm	20.3dB@-15dBm	20.8dB@-17dBm	21.3dB@-19dBm	26 000ps/nm

# Summary

## 400G-ZR+

- 400G-ZR+ is a > 120km long haul solution
  - Low optical output power → not compatible with most brownfield long haul line systems
  - Not compatible with every platform due to power and thermal constraints
  - Transceivers vary between 18W and 25W - it is very inconsistent
  - **Using those transceiver in unsupported platforms could irreversibly damage your device!**
- 400G-ZR+ with > 0dBm Tx power is compatible with most long-haul line systems
  - 400G-ZR+ transceivers with > 0dBm Tx power not available yet
  - **Even higher power consumption, so always check platform support as this could irreversibly damage your device!**
  - Customer needs to test & validate 3rd party line systems w/ their optical vendors

# Questions?



The background of the slide is a dark blue aerial night view of a city, with a white network overlay consisting of numerous interconnected nodes and lines, resembling a data network or fiber optic layout. The word 'ARISTA' is faintly visible in the top left corner in a large, light blue font.

# Thank you for your attention!

Florian Hibler  
Manager, Systems Engineering  
Arista Networks, Inc.

(e) [florian@arista.com](mailto:florian@arista.com)  
(m) +49 171 7576089  
(w) <http://www.arista.com>

# URL reference

## 400G-ZR

- Arista 400G-ZR Line System
  - [https://www.arista.com/assets/data/pdf/Datasheets/400ZR\\_DCI\\_Solution\\_Datasheet.pdf](https://www.arista.com/assets/data/pdf/Datasheets/400ZR_DCI_Solution_Datasheet.pdf)
- Datwyler Datasheet Single Mode Fiber OS2 / G.652.D
  - [https://itinfra.datwyler.com/wp-content/uploads/2020/05/Single-mode-fibre-E9\\_125\\_250-OS2--G.652.D\\_en.pdf](https://itinfra.datwyler.com/wp-content/uploads/2020/05/Single-mode-fibre-E9_125_250-OS2--G.652.D_en.pdf)

## 400G-ZR+

- OpenZR+ Specifications
  - <http://openzrplus.org/documents/>
- SmartOptics Datasheet SO-TQSFPDD4CCZRP
  - [https://www.smartoptics.com/wp-content/uploads/2021/07/SO-TQSFPDD4CCZRP\\_R5.3.pdf](https://www.smartoptics.com/wp-content/uploads/2021/07/SO-TQSFPDD4CCZRP_R5.3.pdf)
- Arista 400G-ZR+ TOI
  - <https://www.arista.com/en/support/toi/eos-4-26-2f/14839-400gbase-zrp-support-toi>